



Current cables and Sense cables with TTA clamps (combined)

Current cables with battery clamps
Sense cables with alligator clamps



Transport case with included device accessories and cables



Current cables and Sense cable with Kelvin probes



Power supply adapter



Power supply adapter (car charger)

Order info

- **RMO-H1 model** (up to 100 A DC)

Instrument with included accessories	Article No
Handheld Micro Ohmmeter RMO-H1	RMOH100-N-00
<ul style="list-style-type: none"> - USB with DV-Win PC software - Ground (PE) cable - Carrying belts - Plastic transport case 	
Power supply adapter 3 A EU	PWR-ADP3A-EU

Recommended accessories RMO-H1	Article No
Current and sense cables 1,3 m with TTA clamps	CS2-1Z3-10CLWC

Optional accessories RMO-H1	Article No
Current and sense cables 1,3 m with Kelvin probes	CS2-1Z3-10CLKP
Current and sense cables 1,3 m (red) and 3 m (black) with TTA clamps	CS-1Z33-10CLWC
Current and sense cables 1,3 m (red) and 5 m (black) with TTA clamps	CS-1Z35-10CLWC
Current and sense cables 5 m with TTA clamps	CS2-05-10CLWC
Current cables 2 x 1,3 m 10 mm ² with battery clamps	C2-1Z3-10CLB1
Sense cables 2 x 1,3 m with alligator clamps (A2)	S2-1Z3-02BPA2
Current cables 1,3 m and 3 m 10 mm ² with battery clamps	C-1Z33-10CLB1

Sense cables 1,3 m and 3 m with alligator clamps (A2)	S-1Z33-02BPA2
Current cables 1,3 m and 5 m 10 mm ² with battery clamps	C-1Z35-10CLB1
Sense cables 1,3 m and 5 m with alligator clamps (A2)	S-1Z35-02BPA2
Current cables 2 x 5 m 10 mm ² with battery clamps	C2-05-10CLB1
Sense cables 2 x 5 m with alligator clamps (A2)	S2-05-02BPA2
Current cables 2 x 10 m 16 mm ² with battery clamps	C2-10-16CLB1
Sense cables 2 x 10 m with alligator clamps (A2)	S2-10-02BPA2
Test shunt 240 μΩ (250 A/60 mV)	SHUNT-240-MK
Test shunt 1 mΩ (150 A/150 mV)	SHUNT-150-MK
Power supply adapter (car charger)	PWR-ADP3-CC0

* **test leads with up to 20 m length are available on request.**

- **RMO-H2 model** (up to 220 A DC)

Instrument with included accessories	Article No
Handheld Micro Ohmmeter RMO-H2	RMOH220-N-00
<ul style="list-style-type: none"> - USB with DV-Win PC software - Ground (PE) cable - Carrying belts - Plastic transport case 	
Power supply adapter 3 A EU	PWR-ADP3A-EU

Recommended accessories RMO-H2	Article No
Current and sense cables 1,3 m with TTA clamps (220 A rated)	CS2-1Z3-10CLWC

Optional accessories RMO-H2	Article No
Current and sense cables 1,3 m with Kelvin probes (220 A rated)	CS2-1Z3-10CLKP
Current and sense cables 1,3 m (red) and 3 m (black) with TTA clamps (220 A rated)	CS-1Z33-16CLWC
Current and sense cables 1,3 m (red) and 5 m (black) with TTA clamps (200 A rated)	CS-1Z35-16CLWC
Current and sense cables 5 m with TTA clamps (200 A rated)	CS2-05-25CLWC
Current cables 2 x 1,3 m 10 mm ² with battery clamps (220 A rated)	C2-1Z3-10CLB1
Sense cables 2 x 1,3 m with alligator clamps (A2)	S2-1Z3-02BPA2
Current cables 1,3 m and 3 m 16 mm ² with battery clamps (220 A rated)	C-1Z33-16CLB1
Sense cables 1,3 m and 3 m with alligator clamps (A2)	S-1Z33-02BPA2
Current cables 1,3 m and 5 m 16 mm ² with battery clamps (200 A rated)	C-1Z35-16CLB1
Sense cables 1,3 m and 5 m with alligator clamps (A2)	S-1Z35-02BPA2
Current cables 2 x 5 m 25 mm ² with battery clamps (200 A rated)	C2-05-25CLB1
Sense cables 2 x 5 m with alligator clamps (A2)	S2-05-02BPA2
Current cables 2 x 10 m 35 mm ² with battery clamps (180 A rated)	C2-10-35CLB1
Sense cables 2 x 10 m with alligator clamps (A2)	S2-10-02BPA2
Test shunt 240 μΩ (250 A/60 mV)	SHUNT-240-MK
Test shunt 1 mΩ (150 A/150 mV)	SHUNT-150-MK
Power supply adapter (car charger)	PWR-ADP3-CC0

* **test leads with up to 20 m length are available on request. The maximum output current in this case will be up to 100 A.**

- **RMO-H3 model** (up to 300 A DC)

Instrument with included accessories	Article No
Handheld Micro Ohmmeter RMO-H3	RMOH300-N-00
<ul style="list-style-type: none"> - USB with DV-Win PC software - Ground (PE) cable - Carrying belts - Plastic transport case 	
Power supply adapter 3 A EU	PWR-ADP3A-EU

Recommended accessories RMO-H3	Article No
Current and sense cables 1,3 m with TTA clamps (300 A rated)	CS2-1Z3-25CLWC

Optional accessories RMO-H3	Article No
Current and sense cables 1,3 m with Kelvin probes (270 A rated)	CS2-1Z3-16CLKP
Current and sense cables 1,3 m (red) and 3 m (black) with TTA clamps (270 A rated)	CS-1Z33-25CLWC
Current and sense cables 1,3 m (red) and 3 m (black) with TTA clamps (290 A rated)	CS-1Z33-35CLWC
Current and sense cables 1,3 m (red) and 5 m (black) with TTA clamps (240 A rated)	CS-1Z35-25CLWC
Current and sense cables 1,3 m (red) and 10 m (black) with TTA clamps (220 A rated)	CS-1Z310-35CLWC
Current cables 2 x 1,3 m 25 mm ² with battery clamps (300 A rated)	C2-1Z3-25CLB1
Sense cables 2 x 1,3 m with alligator clamps (A2)	S2-1Z3-02BPA2
Current cables 1,3 m and 3 m 25 mm ² with battery clamps (270 A rated)	C-1Z33-25CLB1
Sense cables 1,3 m and 3 m with alligator clamps (A2)	S-1Z33-02BPA2
Current cables 1,3 m and 3 m 35 mm ² with battery clamps (290 A rated)	C-1Z33-35CLB1
Sense cables 1,3 m and 3 m with alligator clamps (A2)	S-1Z33-02BPA2
Current cables 1,3 m and 5 m 25 mm ² with battery clamps (240 A rated)	C-1Z35-25CLB1
Sense cables 1,3 m and 5 m with alligator clamps (A2)	S-1Z35-02BPA2
Current cables 1,3 m and 10 m 35 mm ² with battery clamps (220 A rated)	C-1Z310-35CLB1
Sense cables 1,3 m and 10 m with alligator clamps (A2)	S-1Z310-02BPA2
Current cables 2 x 5 m 35 mm ² with battery clamps (230 A rated)	C2-05-35CLB1
Sense cables 2 x 5 m with alligator clamps (A2)	S2-05-02BPA2
Current cables 2 x 10 m 50 mm ² with battery clamps (200 A rated)	C2-10-50CLB1
Sense cables 2 x 10 m with alligator clamps (A2)	S2-10-02BPA2
Test shunt 240 $\mu\Omega$ (250 A/60 mV)	SHUNT-240-MK
Test shunt 1 m Ω (150 A/150 mV)	SHUNT-150-MK
Power supply adapter (car charger)	PWR-ADP3-CC0

*** test leads with up to 20 m length are available on request. The maximum output current in this case will be up to 100 A**



Tel: (81) 9688-1000 /01 /02 & 03

Correo: widagg@widagg.com.mx

Página: www.widagg.com.mx

“Llevando confiabilidad a las mediciones de Amper, Volt, Ohm”.