



Current and Sense cables with TTA clamps



Voltage Sense cables with TTA clamps



Device bag



Cable plastic case



Current connection cable with TTA clamps



Cable bag



Transport case



Test shunt

Order Info

| Instrument with Included accessories | Article No |
|--|--------------|
| Winding Ohmmeter RMO-TW | RMOXXTW-N-00 |
| DV-Win PC software including USB cable | |
| Mains Power cable | |
| Ground (PE) cable | |

| Recommended | Article No |
|---|--------------|
| Current cables 2 x 10 m 10 mm ² (32.8 ft, 7 AWG) and Sense cables 2 x 10 m (32.8 ft) with TTA clamps* | CS-10-10LMWC |
| Current cables 2 x 10 m 2,5 mm ² (32.8 ft, 13 AWG) and Sense cables 2 x 10 m (32.8 ft) with TTA clamps** | CS-10-02BPWC |
| Sense cables 2 x 10 m (32.8 ft) with TTA clamps | S2-10-02BPWC |
| Current connection cable 1 x 5 m 10 mm ² (16.4 ft, 7 AWG) with TTA clamps* | CX-05-102XWC |
| Current connection cable 1 x 5 m 6 mm ² (16.4 ft, 9 AWG) with TTA clamps** | CX-05-062XWC |
| Transport case | HARD-CASE-ME |

*Recommended for RMO30TW and RMO50TW

** Recommended for RMO10TW and RMO20TW

| Optional | Article No |
|---|--------------|
| Test shunt 150 A / 150 mV | SHUNT-150-MK |
| Thermal printer 80 mm (3.15 in) (built-in) | PRINT-080-00 |
| Cable plastic case – small size | CABLE-CAS-01 |
| Cable plastic case – medium size | CABLE-CAS-02 |
| Cable bag | CABLE-BAG-00 |
| Current cables 2 x 15 m 10 mm ² (49.2 ft, 7 AWG) and Sense cables 2 x 15 m (49.2 ft) with TTA clamps | CS-15-10LMXC |
| Current cables 2 x 15 m 2,5 mm ² (49.2 ft, 13 AWG) and Sense cables 2 x 15 m (49.2 ft) with TTA clamps | CS-15-02BPWC |
| Current cables 2 x 20 m 16 mm ² (65.6 ft, 5 AWG) and Sense cables 2 x 20 m (65.6 ft) with TTA clamps | CS-20-10LMXC |
| Current cables 2 x 20 m 2,5 mm ² (65.6 ft, 13 AWG) and Sense cables 2 x 20 m (65.6 ft) with TTA clamps | CS-20-02BPWC |
| Sense cables 2 x 15 m (49.2 ft) with TTA clamps | S2-15-02BPWC |
| Sense cables 2 x 20 m (65.6 ft) with TTA clamps | S2-20-02BPWC |
| Current connection cable 1 x 12 m 10 mm ² (39.4 ft, 5 AWG) with TTA clamps | CX-12-102XWC |
| Current connection cable 1 x 12m 6 mm ² (39.4.4 ft, 9 AWG) with TTA clamps | CX-12-062XWC |
| PT100 temperature indicator | TI-000-PT100 |



Tel: (81) 9688-1000 /01 /02 & 03

Correo: widagg@widagg.com.mx

Pagina: www.widagg.com.mx

“Llevando confiabilidad a las mediciones de Amper, Volt, Ohm”.